

Xtend+Climb® Plus Series



Common Dimensions

Rung Pitch	300
Rung Depth	38
Top Width	451

Product Dimensions

PRODUCT SKU	APPROX. WORKING HEIGHT	LAST CLIMBING HEIGHT	RUNG COUNT	MAX. EXTENDED LENGTH	CLOSED LENGTH	WIDTH	DEPTH	WEIGHT (NETT KG)
1303-015	3,314	1,714	9	2,614	743	471	94	8.4
1303-050	3,875	2,275	11	3,175	768	479	102	10.6
1303-010	4,460	2,860	13	3,760	817	487	108	13.0

Technical Description

Xtend+Climb® Plus Series has been developed specifically for the professional contractor or surveyor. The ergonomic design means you can quickly and easily adjust the Xtend+Climb® rung by rung, to exactly the height you need. The tubular section is manufactured from aerospace aluminium with heavy-duty nylon couplings and secure lock tabs that fit your thumbs better for smooth and responsive adjustment.

- » Extends and locks rung by rung
- » Reinforced nylon couplings
- » Precision engineered aerospace grade aluminium
- » Compacts down for ease of storage
- » Padded carry handle
- » Clean-touch anodised finish

Standards & Classification

- » Maximum Static Vertical Load 150kg
- » Conforms to EN 131

Warranty

- » 1 Year

Shipping Dimensions

PRODUCT SKU	SHIPPING LENGTH	SHIPPING WIDTH	SHIPPING DEPTH	SHIPPING VOLUME (M ³)	SHIPPING WEIGHT (GROSS KG)	BARCODE
1303-015	790	510	120	0.0483	9.7	5060169489721
1303-050	800	510	135	0.0551	12.0	5060169489998
1303-010	850	530	140	0.0631	14.5	5060169480001

Notes

All dimensions stated in mm unless marked otherwise. Engineering tolerance +/- 10% or 10mm, whichever is greater. Where applicable, approximate working height is calculated as 1,600mm + Last Climbing Height (4th rung from the ladder top) or the Platform Height.